

Description:

Architectural, a member of the Firefly family, Firefly XL Surface Can offers a simple clean aesthetic available in various colour temperatures, optics, finishes and control options. Firefly XL Surface Can shares the technical features of the remainder of the Firefly family ensuring consistent illumination whilst being controllable for the desired ambience. A luminaire which provides sought after energy efficiency and product longevity.



Technical:

LED type	Vero 13	Control gear	Remote
Rated power	18w	Dimming protocols	Dali, 0-10V, Phase Dim, On/Off
CRI	80	Cable length	300 mm
Beam angles	Nominated in table below	Mounting options	Surface
Input power	500mA/36v	Weight	1-2 kg
Nominal lumens	1,200lm	Hardware	Glass lens, O-Ring, Gland, Cable
IP rating	IP65	Construction	Machined metal & Heat sink
Colour temperature	2700K – 3000K – 4000K	Warranty	Two years

Product Generator: example NL-7024-BR-W-40-SM-18W-1-1

Model	Finish	Beam Angle	CCT	Mounting	Wattage	Dimming	Accessories
NL-7024	AB Aged brass	N Narrow 10°	27 2700K	SM Surface	18w/500mA	1 Dali	1 Honeycomb louver
	BR Brushed brass	M Medium 21°	30 3000K			2 0-10V	2 Diffuser lens
	PB Black	W Wide 33°	40 4000K			3 Phase	3 Elliptical lens 26° x 41°
	PW White					4 On/Off	
	CC Custom						

Order Code

NL-7024				SM			
---------	--	--	--	----	--	--	--