

**Description:**

Surface mounted LED 'puck' light with in-direct light source. Machined in solid brass with machined acrylic backing to create diffused glow on the surface. Available in brass, Aged Brass or standard Black and White. Custom finishes are available upon request. Available in various colour temperatures, IP44 rated.



**Technical:**

LED TYPE	CREE XLamp XP-G3 White	CONTROL GEAR	REMOTE
RATED POWER	1W	DIMMING PROTOCOL	DALI - 0-10V - PHASE DIM - ON/OFF
CRI	80	CABLE LENGTH	500MM STANDARD LENGTH
BEAM ANGLES	NOMINATED IN TABLE BELOW	MOUNTING OPTIONS	SURFACE WALL
INPUT POWER	350mA / 2.73V	WEIGHT	0.5KG
NOMINAL LUMENS	155lm	HARDWARE	ACRYLIC DIFFUSER, CABLE
IP RATING	IP44	CONSTRUCTION	MACHINED METAL & HEATSINK
COLOUR TEMPERATURE	2700K - 3000K - 4000K	WARRANTY	2 YEARS

**Product Generator:** example NL1800-AB-D-30-W-1W-DALI-N/A

Model	Finish	Beam Angle	CCT	Mounting	Wattage	Dimming	Accessory
NL1800	AB Aged Brass	D Diffused	27 2700K	W Wall Mounted	1W / 350mA	DALI	N/A
	BR Brushed Brass		30 3000K			0-10V	
	PB Black		40 4000K			Phase	
	PW White					On/Off	
	CC Custom						

NL1800	-	-	-	-	-	-	-
--------	---	---	---	---	---	---	---