

KOWARI PENDANT

Data Sheet

Description:

An Australian manufactured luminaire coupled with a locally produced LED engine; the Kowari Pendant offers an aged brass or powder coated finish augmented by a selection of shades designed to enhance the luminaires unique display environment.



Technical:

LED type	Cree XHP-50-2	Control gear	Remote
Rated power	4w, 6w	Dimming protocols	Dali, 0-10V, Phase Dim, On/Off
CRI	80	Cable length	300 mm
Beam angles	Diffused	Mounting options	Surface
Input power	350mA – 700mA	Weight	2 kg
Nominal lumens	300lm or 476lm	Hardware	Covert Mounting System
IP rating	IP20	Construction	Machined metal, glass shade
Colour temperature	2700K – 3000K – 4000K	Warranty	Two years

Product Generator: Example NL-1333CC-AB-SF-30-SM-4W-4-N/A

Model	Finish	Shade	CCT	Mounting	Wattage	Dimming	Accessories
NL-1333CC	AB Aged brass	SF Surf mist	27 2700K	SM Surface	4w/350mA	1 Dali	N/A
	BR Brushed brass	PB Black texture	30 3000K		6w/700mA	2 0-10V	
	PB Black	PW White texture	40 4000K			3 Phase	
	PW White	CC Custom				4 On/Off	
	CC Custom						

Order Code

NL-1333CC		SM		N/A