

FIREFLY SQUARE FIXED DOWN

Data Sheet

Description:

A new member of the Firefly family, Firefly Square Fixed Down offers a simple clean aesthetic, produced in a range of colour temperatures, optics, finishes and control options. Firefly Square Fixed Down shares the technical features of the remainder of the Firefly family ensuring consistent illumination, product quality and configuration.



Technical:

LED type	Cree XHP50-2	Control gear	Remote
Rated power	4w, 6w or 9w	Dimming protocols	Dali, 0-10V, Phase Dim, On/Off
CRI	80	Cable length	300 mm
Beam angles	Nominated in table below	Mounting options	Surface
Input power	Nominated in the table below	Weight	1.1 kg
Nominal lumens	300lm – 476lm – 780lm	Hardware	Covert Mounting System
IP rating	IP65	Construction	Machined metal, glass lens
Colour temperature	2700K – 3000K – 4000K	Warranty	Two years

Product Generator: example NL-6007-AB-M-30-SM-8W-4-N/A

Model	Finish	Beam Angle	CCT	Mounting	Wattage	Dimming	Accessories
NL-6007CC	AB Aged brass	N Narrow 10°	27 2700K	SM Surface	4w/350mA	1 Dali	N/A
	BR Brushed brass	M Medium 21°	30 3000K		6w/700mA	2 0-10V	
	PB Black	W Wide 33°	40 4000K		9w/1050mA	3 Phase	
	PW White					4 On/Off	
	CC Custom						
NL-6007CV	AB Aged brass	N Narrow 10°	27 2700K	SM Surface	4w/24 VDC	On/Off	N/A
	BR Brushed brass	M Medium 21°	30 3000K		6w/24 VDC		
	PB Black	W Wide 33°	40 4000K		9w/24 VDC		
	PW White						
	CC Custom						

Order Code

NL-6007				SM			N/A
---------	--	--	--	----	--	--	-----